


Standard / Norm : SRPS EN 10060: 2003
Materijal / Material : S235JR; S275JR; S355JR
ili po zahtevu klijenta / or at client's request



	G	d	A		G	d	a
	[kg / m]	[mm]	[mm² x 10²]		[kg / m]	[mm]	[mm² x 10²]
R 10	0.617	10	0.785	R 47	13.6	47	17.3
R 12	0.888	12	1.13	R 48	14.2	48	18.1
R 14	1.21	14	1.54	R 49.2	14.9	49.2	19
R 16	1.58	16	2.01	R 50	15.4	50	19.6
R 18	2	18	2.54	R 51	16	51	20.4
R 20	2.47	20	3.14	R 52	16.7	52	21.2
R 22	2.98	22	3.8	R 53	17.3	53	22.1
R 22.5	3.05	22.25	3.89	R 54	18	54	22.9
R 23.6	3.43	23.6	4.37	R 55	18.7	55	23.8
R 24	3.55	24	4.52	R 55.8	19.2	55.8	24.5
R 24.5	3.7	24.5	4.71	R 56	19.3	56	24.6
R 25	3.85	25	4.91	R 57	20	57	25.5
R 26	4.17	26	5.31	R 58	20.7	58	26.4
R 26.7	4.4	26.7	5.6	R 59	21.5	59	27.3
R 27	4.49	27	5.73	R 60	22.2	60	28.3
R 28	4.83	28	6.16	R 62	23.7	62	30.2
R 29	5.19	29	6.61	R 63	24.5	63	31.2
R 29.5	5.37	29.5	6.83	R 65	26	65	33.2
R 29.7	5.44	29.7	6.93	R 70	30.2	70	38.5
R 30	5.55	30	7.07	R 75	34.7	75	44.2
R 31	5.92	31	7.55	R 80	39.5	80	50.3
R 32	6.31	32	8.04	R 85	44.5	85	56.7
R 34	7.13	34	9.08	R 90	49.9	90	63.6
R 34.4	7.3	34.4	9.29	R 95	55.6	95	70.9
R 35	7.55	35	9.62	R 100	61.7	100	78.5
R 35.7	7.86	35.7	10	R 105	68	105	86.6
R 36	7.99	36	10.2	R 110	74.6	110	95
R 37	8.44	37	10.8	R 120	88.8	120	113
R 38	8.9	38	11.3	R 130	104	130	133
R 39	9.38	39	11.9				
R 39.2	9.47	39.2	12.1				
R 40	9.86	40	12.6				
R 42	10.9	42	13.9				
R 44	11.9	44	15.2				
R 45	12.5	45	15.9				
R 46	13	46	16.6				